

ENDU[®] COMBI RA

REGIONAL ALL POSITION TIRE



Copyright © 2023 Apollo Tires

APOLLO TIRES (US) INC.
6 Concourse Parkway Building 6
Suite 2920
Atlanta, GA 30328
+1 (877) 234 0867
contact.us@apollotyres.com



ENDU[®] COMBI RA

THE ENDU[®] COMBI RA REGIONAL ALL POSITION TIRE OFFERS EXCEPTIONAL PERFORMANCE & CASING DURABILITY.




M + S



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	ORIGINAL TREAD DEPTH (1/32")	STATIC LOADED RADIUS (INCH)	RECOMMENDED RIM WIDTH (INCH)	ALTERNATE RIM WIDTH (INCH)	TIRE WEIGHT		LOAD DETAILS (LBS)	
												LBS	KG	SINGLE	DUAL
2021100	215/75R17.5	14	G	126/124	M	30.3	8.3	16	14.2	6.00	6.75	60.7	27.5	3750 lbs @ 105 psi	3525 lbs @ 105 psi
2021101	235/75R17.5	14	G	132/130	M	31.6	9.4	18	14.7	6.75	7.50	68.1	30.9	4410 lbs @ 115 psi	4190 lbs @ 115 psi
2021102	245/70R17.5	14	G	136/134	M	31.1	9.7	18	14.5	7.50	6.75	76.1	34.5	4940 lbs @ 125 psi	4675 lbs @ 125 psi
*2021104	225/70R19.5	14	G	128/126	L	32.2	8.9	16	14.9	6.75	6.00	71.0	32.2	3970 lbs @ 110 psi	3750 lbs @ 110 psi
*2021103	225/70R19.5	16	H	130/128	L	32.2	8.9	16	14.9	6.75	6.00	71.0	32.2	4190 lbs @ 120 psi	3970 lbs @ 120 psi
*2021113	265/70R19.5	14	G	140/138	M	34.0	10.3	15	15.8	7.50	8.25	92.4	41.9	5510 lbs @ 112 psi	5205 lbs @ 112 psi
2021106	11R22.5	14	G	144/142	L	41.2	11.1	20	19.3	8.25	7.50	129.0	58.5	6175 lbs @ 105 psi	5840 lbs @ 105 psi
2021105	11R22.5	16	H	146/143	L	41.2	11.1	20	19.3	8.25	7.50	129.0	58.5	6610 lbs @ 120 psi	6005 lbs @ 120 psi
2021107	255/70R22.5	16	H	140/137	M	36.6	9.9	17	17.1	7.50	6.75	129.0	42.9	5510 lbs @ 120 psi	5070 lbs @ 120 psi
*2021108	275/70R22.5	18	J	148/145	L	37.4	10.8	17	17.5	8.25	7.50	116.6	52.9	6940 lbs @ 130 psi	6395 lbs @ 130 psi
2021110	295/75R22.5	14	G	144/141	L	40.2	11.5	20	18.7	9.00	8.25	127.4	57.8	6175 lbs @ 110 psi	5675 lbs @ 110 psi
2021109	295/75R22.5	16	H	149/146	L	40.2	11.5	20	18.7	9.00	8.25	127.4	57.8	7160 lbs @ 123 psi	6610 lbs @ 123 psi
2021112	11R24.5	14	G	146/143	L	43.3	11.2	21	20.2	8.25	7.50	140.9	63.9	6610 lbs @ 105 psi	6005 lbs @ 105 psi
2021111	11R24.5	16	H	149/146	L	43.3	11.2	21	20.2	8.25	7.50	140.9	63.9	7160 lbs @ 120 psi	6610 lbs @ 120 psi


*Coming soon

1 ENHANCED STABILITY



Tapered sinusoidal grooves facilitate additional reinforcement on continuous channelized ribs therefore enhancing vehicle stability.

3 EVEN WEAR




Deep stress relieving sipes assists in maintaining even wear and higher removal mileages.

2 IMPROVED TRACTION



- Deep 3D sipes provide excellent traction throughout the tread life.
- Zig-Zag grooved walls help provide optimized biting edges for excellent traction in all seasonal conditions.

4 MULTIPLE RETREADS



Robust construction with optimized belt package.